



AA - 4 Pin Lemo Connector					
Size	Max Temp	Volts	Ahr	Part No.	Products
AA	85°C	3.6	1.9	100407	3/4" Piezo (Standard, Welded RTD) 3/4" Quartz 1" Side Pocket Geothermal
	150°C		1.6	100408	
	200°C		1.5	100409	
2 X AA	85°C		3.8	100410	
	150°C		3.2	100411	
	200°C		3.0	100412	

C - 4 Pin Lemo Connector					
Size	Max Temp	Volts	Ahr	Part No.	Products
C	125°C	3.6	7.5	100498	1-1/4" Piezo (Standard, RTD, Welded III)
	150°C		6.2	100671	
	165°C		6.2	100499	
	180°C		5.0	100500	
2 X C	125°C		15.0	100809	
	150°C		12.4	100810	
	165°C		12.4	100811	
	180°C		10.0	100812	

C - Threaded Locking 4 Pin Lemo Connector					
Size	Max Temp	Volts	Ahr	Part No.	Products
C	125°C	3.6	7.5	101268	1-3/8" Piezo (Welded)
	165°C		6.2	101269	
	180°C		5.0	101270	
	200°C		4.5	101271	
2 X C	125°C		15.0	101661	
	165°C		12.4	101662	
	180°C		10.0	101663	
	200°C		9.0	101664	

C - 4 Pin Amphinol Connector					
Size	Max Temp	Volts	Ahr	Part No.	Products
3 X C	85°C	10.8	7.0	100200	2-3/8" Quick Shut In Tool 3-1/2" Quick Shut In Tool
	150°C		6.2	100639	
	165°C		6.2	100203	
	200°C		4.5	100204	
6 X C	85°C		14.0	101665	
	150°C		12.4	101666	
	165°C		12.4	101560	
	200°C		9.0	101667	

Sub CC - Threaded Locking 4 Pin Lemo Connector					
Size	Max Temp	Volts	Ahr	Part No.	Products
Sub CC	150°C	3.6	10.0	100808	1-1/4" Piezo (Welded II) 1-1/4" Quartz
	165°C		9.0	100226	
	200°C		6.2	100227	
2 X Sub CC	150°C		20.0	101660	
	165°C		18.0	101000	
	200°C		12.4	101001	