



1/8" OD Wire

- ✦ 316SS Armor
 - 0.024" Wall Triple Tube = 20,000psi
- ✦ Inconel 825 Armor
 - 0.024" Wall Triple Tube = 20,000psi
- ✦ Encapsulation (Optional)
 - Size
 - 0.25" Round
 - Material
 - Polypropylene = Standard
 - Santoprene
 - Rislant = Diesel Protection
- ✦ Insulation
 - Teflon = 2000°C Max
- ✦ Conductor
 - 22 AWG (Solid)
 - 18 AWG (Solid)
 - 16 AWG (Solid)

1/4" OD Wire

- ✦ 316SS Armor
 - 0.028" Wall = 17,500psi
 - 0.035" Wall = 25,000psi
 - 0.049" Wall = 32,500psi
- ✦ Inconel 825 Armor
 - 0.028" Wall = 20,000psi
 - 0.035" Wall = 27,500psi
 - 0.049" Wall = 35,000psi
- ✦ Encapsulation (Optional)
 - Size
 - 11mm x 11mm
 - 0.375" Round
 - Material
 - Polypropylene = Standard
 - Santoprene
 - Rislant = Diesel Protection
- ✦ Insulation
 - Halar E = 100°C Max
 - Halar P = 150°C Max
 - Teflon = 2000°C Max
- ✦ Conductor
 - 18 AWG (Solid)
 - 18 AWG (7 Strands)
 - 16 AWG (Solid)