





#### Features

-  Fully Welded Construction
-  Hermetically Sealed
-  Dual Protection Metal to Metal Seal Design
-  Dual Axis Vibration Sensor Option
  - Capable Of Monitoring Pump Wear

Piezo Permanent II - Stainless			
Pressure	Temperature	Wire Size	Part No.
750 psi	100°C	1/4"	102575
1,500 psi			102576
3,000 psi	125°C		102577
6,000 psi	150°C		102578
10,000 psi			102579
15,000 psi			102580
750 psi	100°C	1/8"	102599
1,500 psi	125°C		102600
3,000 psi			102601
6,000 psi	150°C		102602
10,000 psi			102603
15,000 psi			102604

Piezo Permanent II With Vibration - Stainless			
Pressure	Temperature	Wire Size	Part No.
750 psi	100°C	1/4"	102564
1,500 psi			102565
3,000 psi	125°C		102300
6,000 psi			102299
10,000 psi			102283
15,000 psi	100°C		102566
750 psi		102568	
1,500 psi		102569	
3,000 psi	125°C	1/8"	102570
6,000 psi			102571
10,000 psi			102572
15,000 psi			102573

Specifications		
	Pressure	Temperature
<b>Accuracy Up To</b>	0.022% Full Scale	0.25°C
<b>Resolution</b>	0.0003% Full Scale	0.005°C
<b>Drift</b>	< 3 psi / year	< 0.1°C / year
<b>Vibration Range</b>	+/- 50 g	