


#### Features

- ✦ One Leak Path
  - Metal to Metal C-Ring
  - Triple O-Ring 200°C Option
- ✦ Modular Memory Cartridge
- ✦ 2 Million Sample Capacity
- ✦ Inconel 718 / MP35N – NACE MR0175
- ✦ Fast Response



1.25" OD Quartz DXB 2 Memory Tool - Inconel 718		
Pressure	Temperature	Part No.
10,000 psi	150°C	100017
16,000 psi	150°C	101695
16,000 psi	177°C	101696
16,000 psi	200°C	101697
20,000 psi	177°C	101698
20,000 psi	200°C	101699

Accessory Type	Part No.
Replaceable Memory Module 177°C	100024
Replaceable Memory Module 200°C	100765
Bullnose Inconel 718	100128
Crossover 0.75-16 Inconel 718	100129
Crossover 0.25 NPT Inconel 718	100130
USB To Serial Converter Assembly	100682
Redress Kit Viton 90	101693
Redress Kit Aflas	101694
Redress Kit Chemraz	101685

Specifications		
	Pressure	Temperature
<b>Accuracy</b>	0.020% F.S.	0.25 °C
<b>Resolution</b>	0.00006% F.S.	0.005 °C
<b>Drift</b>	< 3 psi / year	< 0.1 °C / year
<b>Capacity</b>	2 Million Samples	
<b>Communication Method</b>	USB	